according to Regulation (EC) No 1907/2006

# Holzlauge weiß

Print date: 21.12.2016 MSDS code: 0839 Page 1 of 8

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Holzlauge weiß

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Washing and cleaning products (including solvent based products)

# 1.3. Details of the supplier of the safety data sheet

Company name: mafi Naturholzboden GmbH Street: Utzweihstraße 21+25 Place: A-5212 Schneegattern

Telephone: +43 (0)7746 2711-20 Telefax: +43 (0)7746 3747

e-mail: office@mafi.at

Responsible Department: Labor: +43 (0)7746 2711-20

**1.4. Emergency telephone** Vergiftungsinformationszentrale Wien: +43 1 406 43 43

number:

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

### Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Corr. 1A

Serious eye damage/eye irritation: Eye Dam. 1

Hazard Statements:

Causes severe skin burns and eye damage.

## 2.2. Label elements

### **Regulation (EC) No. 1272/2008**

# Hazard components for labelling

Sodium hydroxide; caustic soda

calcium oxide

Signal word: Danger

Pictograms:



# **Hazard statements**

H314 Causes severe skin burns and eye damage.

# **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P363 Wash contaminated clothing before reuse.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see Additional information on this label).

according to Regulation (EC) No 1907/2006

## Holzlauge weiß

Print date: 21.12.2016 MSDS code: 0839 Page 2 of 8

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

#### 2.3. Other hazards

No information available.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### **Chemical characterization**

mixture of Caustic soda and Surfactant

#### **Hazardous components**

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	Classification according to Regulation (EC) No. 1272/2008 [CLP]				
1310-73-2	Sodium hydroxide; caustic soda			1 - < 5 %	
	215-185-5				
	Skin Corr. 1A; H314				
1305-78-8	calcium oxide			1 - < 5 %	
	215-138-9				
	Skin Irrit. 2, Eye Dam. 1, STOT SE 3; H315 H318 H335				

Full text of H and EUH statements: see section 16.

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

#### After inhalation

Provide fresh air. Medical treatment necessary.

#### After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

## After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

according to Regulation (EC) No 1907/2006

# Holzlauge weiß

Print date: 21.12.2016 MSDS code: 0839 Page 3 of 8

#### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

#### 5.2. Special hazards arising from the substance or mixture

Non-flammable.

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

#### Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

### Advice on protection against fire and explosion

No special fire protection measures are necessary.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations.

## Advice on storage compatibility

No special measures are necessary.

# 7.3. Specific end use(s)

Washing and cleaning products (including solvent based products)

#### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

according to Regulation (EC) No 1907/2006

	Holzlauge weiß	
Print date: 21.12.2016	MSDS code: 0839	Page 4 of 8

#### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
1305-78-8	Calcium oxide	-	2		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
1310-73-2	Sodium hydroxide	-	-		TWA (8 h)	WEL
		-	2		STEL (15 min)	WEL
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

### 8.2. Exposure controls

#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

#### Eye/face protection

Suitable eye protection: goggles.

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Wear suitable protective clothing.

# Respiratory protection

In case of inadequate ventilation wear respiratory protection.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: liquid Colour: white

Test method

pH-Value (at 20 °C): > 13

Changes in the physical state

Melting point: not determined Initial boiling point and boiling range:  $> 100 \, ^{\circ}\text{C}$  Flash point:  $> 150 \, ^{\circ}\text{C}$ 

**Flammability** 

Solid: not applicable
Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

according to Regulation (EC) No 1907/2006

	Holzlauge weiß	
Print date: 21.12.2016	MSDS code: 0839	Page 5 of 8

**Auto-ignition temperature** 

Solid: not applicable
Gas: not applicable

Decomposition temperature: not determined

**Oxidizing properties** 

Not oxidizing.

Vapour pressure: not determined

Density (at 20 °C): ca. 1,06 g/cm³

Water solubility: completely miscible

Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Possibility of hazardous reactions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

## 10.3. Possibility of hazardous reactions

Exothermic reaction with: Acid, Peroxide, Oxidising agent.

# 10.4. Conditions to avoid

none

#### 10.5. Incompatible materials

Keep away from: Acid, Oxidising agent, Peroxide.

# 10.6. Hazardous decomposition products

No known hazardous decomposition products.

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

# Additional information on tests

This mixture is classified as hazardous according to 1999/45/EC.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose		[h]   [d]	Species	Source
1310-73-2	Sodium hydroxide; caustic soda					
	Acute fish toxicity	LC50	45,4 mg/l	96 h	Onchorhynchus mykiss	

### 12.2. Persistence and degradability

according to Regulation (EC) No 1907/2006

## Holzlauge weiß

Print date: 21.12.2016 MSDS code: 0839 Page 6 of 8

The product has not been tested.

#### 12.3. Bioaccumulative potential

The product has not been tested.

#### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The product has not been tested.

#### 12.6. Other adverse effects

No information available.

#### **Further information**

Avoid release to the environment.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

### Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

#### Waste disposal number of waste from residues/unused products

200115 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND

INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately

collected fractions (except 15 01); alkalines

Classified as hazardous waste.

# Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

# **SECTION 14: Transport information**

# Land transport (ADR/RID)

14.1. UN number:	: UN 1824

14.2. UN proper shipping name: SODIUM HYDROXIDE, SOLUTION

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Classification code:C5Limited quantity:5 LTransport category:3Hazard No:80Tunnel restriction code:E

# Other applicable information (land transport)

E1

### Marine transport (IMDG)

**14.1. UN number:** UN 1824

14.2. UN proper shipping name: SODIUM HYDROXIDE, SOLUTION

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:-Limited quantity:1 LEmS:F-A, S-B

according to Regulation (EC) No 1907/2006

## Holzlauge weiß

Print date: 21.12.2016 MSDS code: 0839 Page 7 of 8

## Other applicable information (marine transport)

F2

#### Air transport (ICAO)

**14.1. UN number:** UN 1824

14.2. UN proper shipping name: SODIUM HYDROXIDE, SOLUTION

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:A3 A803Limited quantity Passenger:0.5 L

IATA-packing instructions - Passenger: 851
IATA-max. quantity - Passenger: 1 L
IATA-packing instructions - Cargo: 855
IATA-max. quantity - Cargo: 30 L

#### Other applicable information (air transport)

E2

Passenger-LQ: Y840

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

#### 14.6. Special precautions for user

Warning: strongly corrosive.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

### **Additional information**

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

# **National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

## 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**

# Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration. 50%

LD50: Lethal dose, 50%

according to Regulation (EC) No 1907/2006

# Holzlauge weiß

Print date: 21.12.2016 MSDS code: 0839 Page 8 of 8

#### Relevant H and EUH statements (number and full text)

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)