


Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: NI16 9 7300
Print date: 13.07.2023
Version: 32

Neoindustry Holzbodenöl
Revision date: 12.01.2023
Issue date: 12.01.2023

GB
Page 1 / 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. product identifiers

Article No. (manufacturer/supplier) NI16 9 7300
Trade name/designation Neoindustry Holzbodenöl
grau
UFI: 3M30-E0RQ-V003-MPTR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Liquid coating

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/downstream user/distributor):

Odenwälder Lackfabrik GmbH
Werkstrasse 21 Telephone: +49 6063 57710
D-64732 Bad König Telefax: +49 6063 577129

Department responsible for information:

Labor
E-mail (competent person): info@olf-lacke.de

1.4. Emergency telephone number

Only available during office hours. +49 6063 57710

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms

Hazard statements

not applicable

Precautionary statements

not applicable

Hazard components for labelling

not applicable

Supplemental hazard information

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
EUH208 Contains Cobaltbis(2-ethylhexanoate). May produce an allergic reaction.
EUH210 Safety data sheet available on request.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description Öle auf natürlicher Basis

Classification according to Regulation (EC) No 1272/2008 [CLP]

| EC No. | REACH No. | weight-% |
|-----------|---|----------|
| CAS No. | Designation | |
| Index No. | classification // Remark | |
| 918-481-9 | 01-2119457273-39 Hydrocarb., C10-C13, n-alkanes, isoalkanes, cyclenes, <2%aromatics Asp. Tox. 1 H304 / Flam. Liq. 4 H227 / EUH066 | 1 - 2,5 |

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: NI16 9 7300 Neoindustry Holzbodenöl
Print date: 13.07.2023 Revision date: 12.01.2023
Version: 32 Issue date: 12.01.2023

GB
Page 2 / 8

| | | |
|-------------------------|---|-----------|
| 205-249-0 136-51-6 | 01-2119978297-19 Calciumbis(2-ethylhexanoat) Eye Dam. 1 H318 / Repr. 2 H361 | 0,5 - 1 |
| 205-250-6 136-52-7 | 01-2119524678-29 Cobaltbis(2-ethylhexanoate) Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Repr. 1B H360 / Aquatic Acute 1 H400 / Aquatic Chronic 3 H412 | 0,1 - 0,5 |
| 245-018-1 22464-99-9 | 01-2119979088-21 2-Ethylhexanic acid, zirconium salt Repr. 1B H360 | 0,1 - 0,5 |

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it

Article No.: NI16 9 7300
Print date: 13.07.2023
Version: 32

Neoindustry Holzbodenöl
Revision date: 12.01.2023
Issue date: 12.01.2023

GB
Page 3 / 8

for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

not applicable

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: NI16 9 7300
Print date: 13.07.2023
Version: 32

Neoindustry Holzbodenöl
Revision date: 12.01.2023
Issue date: 12.01.2023

GB
Page 4 / 8

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. **Information on basic physical and chemical properties**

| | |
|---|---|
| Physical state: | Liquid |
| Colour: | refer to label |
| Odour: | characteristic |
| Odour threshold: | not applicable |
| Melting point/freezing point: | not applicable |
| Initial boiling point and boiling range: | not applicable |
| Flammability: | Combustible liquid. |
| Lower and upper explosion limit: | |
| Lower explosion limit: | 0,6 Vol-% Source: Hydrocarb., C10-C13, n-alkanes, isoalkanes, cyclenes, <2%aromatics |
| Upper explosion limit: | 7 Vol-% Source: Hydrocarb., C10-C13, n-alkanes, isoalkanes, cyclenes, <2%aromatics |
| Flash point: | > 100 °C |
| Auto-ignition temperature: | 220 °C Source: Hydrocarb., C10-C13, n-alkanes, isoalkanes, cyclenes, <2%aromatics |
| Decomposition temperature: | not applicable |
| pH at 20 °C: | not applicable |
| Cinematic viscosity (40°C): | < 80 mm²/s |
| Viscosity at 20 °C: | 20 s 4 mm Method: DIN 53211 |
| Solubility(ies): | |
| Water solubility at 20 °C: | |
| Partition coefficient: n-octanol/water: | see section 12 |
| Vapour pressure at 20 °C: | 0,4 mbar Source: Hydrocarb., C10-C13, n-alkanes, isoalkanes, cyclenes, <2%aromatics |
| Density and/or relative density: | |
| Density at 20 °C: | 0,96 g/cm³ |
| Relative vapour density: | not applicable |
| particle characteristics: | not applicable |

9.2. **Other information**

| | |
|--------------------------|--------------------|
| Solid content: | 97 weight-% |
| solvent content: | |
| Organic solvents: | 2 weight-% |
| Water: | 0 weight-% |

SECTION 10: Stability and reactivity

10.1. **Reactivity**

No information available.

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to

Article No.: NI16 9 7300
Print date: 13.07.2023
Version: 32

Neoindustry Holzbodenöl
Revision date: 12.01.2023
Issue date: 12.01.2023

GB
Page 5 / 8

section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

| EC No. CAS No. | Designation | Classification according to Regulation (EC) No 1272/2008 [CLP] |
|-------------------------|-------------------------------------|--|
| 205-250-6 136-52-7 | Cobaltbis(2-ethylhexanoate) | Repr. 1B |
| 245-018-1 22464-99-9 | 2-Ethylhexanic acid, zirconium salt | Repr. 1B |

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. Toxicity

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.



Article No.: NI16 9 7300
Print date: 13.07.2023
Version: 32

Neoindustry Holzbodenöl
Revision date: 12.01.2023
Issue date: 12.01.2023

GB
Page 6 / 8

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Dispose of waste according to applicable legislation.

List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 08 01 11

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

No dangerous good in sense of this transport regulation.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

Land transport (ADR/RID) not applicable

Marine pollutant not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code -

Sea transport (IMDG)

EmS-No. not applicable

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

Article No.: NI16 9 7300
Print date: 13.07.2023
Version: 32

Neoindustry Holzbodenöl
Revision date: 12.01.2023
Issue date: 12.01.2023

GB
Page 7 / 8

VOC-value (in g/L): 24

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

| EC No. CAS No. | Designation | REACH No. |
|-------------------------|--|------------------|
| 918-481-9 | Hydrocarb., C10-C13, n-alkanes, isoalkanes, cyclenes, <2%aromatics | 01-2119457273-39 |
| 205-249-0 136-51-6 | Calciumbis(2-ethylhexanoat) | 01-2119978297-19 |
| 205-250-6 136-52-7 | Cobaltbis(2-ethylhexanoate) | 01-2119524678-29 |
| 245-018-1 22464-99-9 | 2-Ethylhexanic acid, zirconium salt | 01-2119979088-21 |

SECTION 16: Other information

Full text of classification in section 3

| | | |
|--------------------------|--------------------------------------|--|
| Asp. Tox. 1 / H304 | Aspiration hazard | May be fatal if swallowed and enters airways. |
| Flam. Liq. 4 / H227 | Flammable liquids | Combustible liquid. |
| Eye Dam. 1 / H318 | Serious eye damage/eye irritation | Causes serious eye damage. |
| Repr. 2 / H361 | Reproductive toxicity | Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard). |
| Eye Irrit. 2 / H319 | Serious eye damage/eye irritation | Causes serious eye irritation. |
| Skin Sens. 1 / H317 | Respiratory or skin sensitisation | May cause an allergic skin reaction. |
| Repr. 1B / H360 | Reproductive toxicity | May damage fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard). |
| Aquatic Acute 1 / H400 | Hazardous to the aquatic environment | Very toxic to aquatic organisms. |
| Aquatic Chronic 3 / H412 | Hazardous to the aquatic environment | Harmful to aquatic life with long lasting effects. |

Abbreviations and acronyms

| | |
|-----------|---|
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| OEL | Occupational Exposure Limit Value |
| BLV | Biological Limit Value |
| CAS | Chemical Abstracts Service |
| CLP | Classification, Labelling and Packaging |
| CMR | Carcinogenic, Mutagenic and Reprotoxic |
| DIN | German Institute for Standardization / German industrial standard |
| DNEL | Derived No-Effect Level |
| EAKV | European Waste Catalogue Directive |
| EC | Effective Concentration |
| EC | European Community |
| EN | European Standard |
| IATA-DGR | International Air Transport Association – Dangerous Goods Regulations |
| IBC Code | International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk |
| ICAO-TI | International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air |
| IMDG Code | International Maritime Code for Dangerous Goods |
| ISO | International Organization for Standardization |
| LC | Lethal Concentration |
| LD | Lethal Dose |
| MARPOL | Maritime Pollution: The International Convention for the Prevention of Pollution from Ships |
| OECD | Organisation for Economic Cooperation and Development |

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

O D E N W Ä L D E R

LACKFABRIK



Article No.: NI16 9 7300 Neoindustry Holzbodenöl
Print date: 13.07.2023 Revision date: 12.01.2023
Version: 32 Issue date: 12.01.2023

GB
Page 8 / 8

| | |
|-------|--|
| PBT | persistent, bioaccumulative, toxic |
| PNEC | Predicted No Effect Concentration |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals |
| RID | Regulations concerning the International Carriage of Dangerous Goods by Rail |
| UN | United Nations |
| VOC | Volatile Organic Compounds |
| vPvB | very persistent and very bioaccumulative |

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.