

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

O D E N W Ä L D E R

**LACKFABRIK**



Article No.: NI16 9 9110  
Print date: 06.07.2023  
Version: 33

Neoindustry Holzbodenöl  
Revision date: 12.01.2023  
Issue date: 12.01.2023

GB  
Page 1 / 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1. **product identifiers**

Article No. (manufacturer/supplier) NI16 9 9110  
Trade name/designation Neoindustry Holzbodenöl  
weiß  
UFI: 4S50-300N-H00G-57DC

1.2. **Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses:**

Liquid coating

1.3. **Details of the supplier of the safety data sheet**

**Supplier (manufacturer/importer/downstream user/distributor):**

Odenwälder Lackfabrik GmbH  
Werkstrasse 21 Telephone: +49 6063 57710  
D-64732 Bad König Telefax: +49 6063 577129

**Department responsible for information:**

Labor  
E-mail (competent person): info@olf-lacke.de

1.4. **Emergency telephone number**

Only available during office hours. +49 6063 57710

**SECTION 2: Hazards identification**

2.1. **Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. **Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**

**Hazard statements**

not applicable

**Precautionary statements**

not applicable

**Hazard components for labelling**

not applicable

**Supplemental hazard information**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.  
EUH208 Contains Cobaltbis(2-ethylhexanoate). May produce an allergic reaction.  
EUH210 Safety data sheet available on request.

2.3. **Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**

3.2. **Mixtures**

**Description** Öle auf natürlicher Basis

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

EC No.	REACH No.	weight-%
CAS No.	Designation	
Index No.	classification // Remark	
918-481-9	01-2119457273-39 Hydrocarb., C10-C13, n-alkanes, isoalkanes, cyclenes, <2%aromatics Asp. Tox. 1 H304 / Flam. Liq. 4 H227 / EUH066	1 - 2,5

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

O D E N W Ä L D E R

**LACKFABRIK**



Article No.: NI16 9 9110 Neoindustry Holzbodenöl  
Print date: 06.07.2023 Revision date: 12.01.2023  
Version: 33 Issue date: 12.01.2023

GB  
Page 2 / 8

205-249-0 136-51-6	01-2119978297-19 Calciumbis(2-ethylhexanoat) Eye Dam. 1 H318 / Repr. 2 H361	0,1 - 0,5
205-250-6 136-52-7	01-2119524678-29 Cobaltbis(2-ethylhexanoate) Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Repr. 1B H360 / Aquatic Acute 1 H400 / Aquatic Chronic 3 H412	0,1 - 0,5
245-018-1 22464-99-9	01-2119979088-21 2-Ethylhexanic acid, zirconium salt Repr. 1B H360	0,1 - 0,5

**Additional information**

Full text of classification: see section 16

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**Following ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

**Unsuitable extinguishing media**

strong water jet

**5.2. Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

**5.3. Advice for firefighters**

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

**6.3. Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it

Article No.: NI16 9 9110  
Print date: 06.07.2023  
Version: 33

Neoindustry Holzbodenöl  
Revision date: 12.01.2023  
Issue date: 12.01.2023

GB  
Page 3 / 8

for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

#### 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

##### Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

##### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

##### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limit values:

not applicable

#### 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

##### Personal protection equipment

##### Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

##### Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374


Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

##### Eye/face protection

Wear closely fitting protective glasses in case of splashes.

##### Body protection

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: NI16 9 9110  
Print date: 06.07.2023  
Version: 33

Neoindustry Holzbodenöl  
Revision date: 12.01.2023  
Issue date: 12.01.2023

GB  
Page 4 / 8

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

**Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

**SECTION 9: Physical and chemical properties**

9.1. **Information on basic physical and chemical properties**

<b>Physical state:</b>	<b>Liquid</b>
<b>Colour:</b>	<b>refer to label</b>
<b>Odour:</b>	<b>characteristic</b>
<b>Odour threshold:</b>	<b>not applicable</b>
<b>Melting point/freezing point:</b>	<b>not applicable</b>
<b>Initial boiling point and boiling range:</b>	<b>not applicable</b>
<b>Flammability:</b>	<b>Combustible liquid.</b>
<b>Lower and upper explosion limit:</b>	
<b>Lower explosion limit:</b>	<b>0,6 Vol-%</b> Source: Hydrocarb., C10-C13, n-alkanes, isoalkanes, cyclenes, <2%aromatics
<b>Upper explosion limit:</b>	<b>7 Vol-%</b> Source: Hydrocarb., C10-C13, n-alkanes, isoalkanes, cyclenes, <2%aromatics
<b>Flash point:</b>	<b>&gt; 100 °C</b>
<b>Auto-ignition temperature:</b>	<b>220 °C</b> Source: Hydrocarb., C10-C13, n-alkanes, isoalkanes, cyclenes, <2%aromatics
<b>Decomposition temperature:</b>	<b>not applicable</b>
<b>pH at 20 °C:</b>	<b>not applicable</b>
<b>Cinematic viscosity (40°C):</b>	<b>&lt; 80 mm<sup>2</sup>/s</b>
<b>Viscosity at 20 °C:</b>	<b>20 s 4 mm</b> Method: DIN 53211
<b>Solubility(ies):</b>	
<b>Water solubility at 20 °C:</b>	
<b>Partition coefficient: n-octanol/water:</b>	<b>see section 12</b>
<b>Vapour pressure at 20 °C:</b>	<b>0,4 mbar</b> Source: Hydrocarb., C10-C13, n-alkanes, isoalkanes, cyclenes, <2%aromatics
<b>Density and/or relative density:</b>	
<b>Density at 20 °C:</b>	<b>0,99 g/cm<sup>3</sup></b>
<b>Relative vapour density:</b>	<b>not applicable</b>
<b>particle characteristics:</b>	<b>not applicable</b>

9.2. **Other information**

<b>Solid content:</b>	<b>97 weight-%</b>
<b>solvent content:</b>	
<b>Organic solvents:</b>	<b>2 weight-%</b>
<b>Water:</b>	<b>0 weight-%</b>

**SECTION 10: Stability and reactivity**

10.1. **Reactivity**

No information available.

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: NI16 9 9110  
Print date: 06.07.2023  
Version: 33

Neoindustry Holzbodenöl  
Revision date: 12.01.2023  
Issue date: 12.01.2023

GB  
Page 5 / 8

section 7.

**10.3. Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

**10.4. Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

**10.5. Incompatible materials**

not applicable

**10.6. Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

Based on available data, the classification criteria are not met.

**Skin corrosion/irritation; Serious eye damage/eye irritation**

Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Based on available data, the classification criteria are not met.

**STOT-single exposure; STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Practical experience/human evidence**

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

**Overall assessment on CMR properties**

EC No. CAS No.	Designation	Classification according to Regulation (EC) No 1272/2008 [CLP]
205-250-6 136-52-7	Cobaltbis(2-ethylhexanoate)	Repr. 1B
245-018-1 22464-99-9	2-Ethylhexanic acid, zirconium salt	Repr. 1B

**11.2. Information on other hazards**

**Endocrine disrupting properties**

No information available.

**SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

**12.1. Toxicity**

Based on available data, the classification criteria are not met.

**12.2. Persistence and degradability**

Toxicological data are not available.

**12.3. Bioaccumulative potential**

Toxicological data are not available.



Article No.: NI16 9 9110  
Print date: 06.07.2023  
Version: 33

Neoindustry Holzbodenöl  
Revision date: 12.01.2023  
Issue date: 12.01.2023

GB  
Page 6 / 8

**12.4. Mobility in soil**

Toxicological data are not available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

No information available.

**12.7. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Appropriate disposal / Product Recommendation**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Dispose of waste according to applicable legislation.

**List of proposed waste codes/waste designations in accordance with EWC**

080112 waste paint and varnish other than those mentioned in 08 01 11

**Appropriate disposal / Package Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**No dangerous good in sense of this transport regulation.**

**14.1. UN number or ID number**

not applicable

**14.2. UN proper shipping name**

**14.3. Transport hazard class(es)**

not applicable

**14.4. Packing group**

not applicable

**14.5. Environmental hazards**

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

**14.6. Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Further information**

**Land transport (ADR/RID)**

Tunnel restriction code

-

**Sea transport (IMDG)**

EmS-No.

not applicable

**14.7. Maritime transport in bulk according to IMO instruments**

No transport as bulk according IBC - Code.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: NI16 9 9110  
Print date: 06.07.2023  
Version: 33

Neoindustry Holzbodenöl  
Revision date: 12.01.2023  
Issue date: 12.01.2023

GB  
Page 7 / 8

VOC-value (in g/L): 26

#### National regulations

#### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

#### 15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
918-481-9	Hydrocarb., C10-C13, n-alkanes, isoalkanes, cyclenes, <2%aromatics	01-2119457273-39
205-249-0 136-51-6	Calciumbis(2-ethylhexanoat)	01-2119978297-19
205-250-6 136-52-7	Cobaltbis(2-ethylhexanoate)	01-2119524678-29
245-018-1 22464-99-9	2-Ethylhexanic acid, zirconium salt	01-2119979088-21

#### SECTION 16: Other information

##### Full text of classification in section 3

Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Flam. Liq. 4 / H227	Flammable liquids	Combustible liquid.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Repr. 1B / H360	Reproductive toxicity	May damage fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic organisms.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.

##### Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

O D E N W Ä L D E R

**LACKFABRIK**



Article No.: NI16 9 9110 Neoindustry Holzbodenöl  
Print date: 06.07.2023 Revision date: 12.01.2023  
Version: 33 Issue date: 12.01.2023

GB  
Page 8 / 8

---

PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

**Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.